



COMPOSIÇÃO: INTERIOR EM BORRACHA SINTÉTICA, SEGUIDO POR UMA TRANÇA DE AÇO E REFORÇADO COM OUTRA CAMADA EXTERNA DE BORRACHA.

TEMPERATURA:

-40° +100°

NORMAS: DIN EN 853, SAE 100R1 AT, ISO 1436

TUBO R1/1SN



INTERIOR



EXTERIOR



MAX. PRESSÃO
DE TRABALHO



PRESSÃO
DE ROTURA



ÂNGULO
DE TRABALHO



PESO

CÓDIGO	NOMINAL	mm	mm	bar	psi	bar	psi	mm	g/m
0301000001	3/16"	4,8	11,8	250	3625	1000	14500	90	180
0301000002	1/4"	6,4	13,4	225	3263	900	13050	100	220
0301000003	5/16"	8	15	215	3118	860	12470	115	260
0301000004	3/8"	9,5	17,4	180	2610	720	10440	130	330
0301000005	1/2"	12,7	20,6	160	2320	640	9280	180	410
0301000006	5/8"	16	23,7	130	1885	520	7540	200	470
0301000007	3/4"	19	27,7	105	1523	420	6090	240	585
0301000008	1"	25,4	35,6	88	1276	352	5104	300	870
0301000009	1 1/4"	31,8	43,5	63	914	252	3654	420	1205
0301000010	1 1/2"	38,1	51	50	725	200	2900	500	1400
0301000011	2"	50,8	64,5	40	580	160	2320	630	1910
(SOB CONSULTA)	2 1/2"	63,5	76,5	40	580	160	2320	762	2535
(SOB CONSULTA)	3"	76,2	88,5	35	508	140	2030	900	2710

